MATERIAL SAFETY DATA SHEET

OSHA 29 CFR 1910.1200

I. Product Identification

All Purpose Sand
All Purpose Gravel

II. Hazardous Ingredients/Identify Information

Hazardous Components CAS NO.
Silica Sand, Crystalline 14808-60-7
Other Limits: National Institute for Occupational Safety and Health (NIOSH) Recommended standard maximum permissible concentration = 0.05 mgfM3 (respirable free silica) as determined by a full-shift sample up to 10 hour working day. 40-hour work week. See NIOSH Criteria for a Recommended Standard Occupational Exposure to Crystalline Silica.

III. Health Hazard Data

This product contains silica particles that may be broken down to respirable size range during shipping, handling, or use, and thus may be inhaled.
Route(s) of Entry: Inhalation, Skin, Ingestion
Health Hazards (Acute and Chronic):
-Contains Silica dust that can cause severe and permanent lung damage and other diseases.
-Breathing silica dust can cause silicosis, a lung disease that can cause serious breathing difficulties and death.
-Breathing silica dust may cause cancer.
-Breathing silica dust may cause scleroderma, a scarring of the skin or internal organs.
Breathing silica dust may not cause noticeable injury or illness, even though permanent lung damage may be occurring.

IV. Emergency and First Aid Procedures

For sand in eyes, wash immediately with water. If irritation persists, seek medical attention. For gross inhalation, remove person immediately to fresh air, give artificial respiration as needed, and seek medical attention as needed.

V. Control Measures! Personal Protection

Inhalation: DO NOT BREATH DUST. In cases where the sand can be used in a damp condition, the most effective dust control measure is to keep the sand damp. Many uses of silica sand require it to be used in dry condition; in such cases PEL exposure limits may be exceeded. Local exhaust can be helpful to reduce airborne dust levels. When dust levels exceed PEL exposure limits, the use of an OSHA, MSA or NIOSH approved respirator is required. Respirator requirements are based on exposure level as shown below:

5 x PEL or less: Any dust respirator.

WARN EMPLOYEES AND/OR CUSTOMERS OF THE HAZARDS AND REQUIRED OSHA PRECAUTIONS ASSOCIATED WITH THE USE OF THIS PRODUCT.

I. Product Identification

Asphalt

II. Composition I Information on Ingredients

Asphalt

III. Potential Health Effects

INHALATION: Inhalation of hot asphalt vapors can produce eye and respiratory tract irritation, headache, nausea and nervousness.
EYE CONTACT: Vapors of hot asphalt may cause eye irritation.
SKIN CONTACT: Handling of hot asphalt can cause severe burns because it is sticky and not readily removed from skin. Vapors from hot asphalt may irritate the skin. Occasional contact with asphalt is not expected to have serious health effects; however repeated contact may cause dermatitis (skin Irritation).
INGESTION: Ingestion of cooled asphalt is relatively non-toxic.

IV. First-Aid Measures

INHALATION: Remove from further exposure. If unconsciousness occurs, seek immediate medical assistance. If breathing stops, use mouth-to-mouth resuscitation.
EYE CONTACT: Flush immediately with water for at least 15 minutes. Seek medical attention immediately.
SKIN CONTACT: If hot asphalt contacts exposed skin, cool immediately with cold water and seek medical assistance promptly. Exercise extreme care in removing contaminated clothing to avoid damage to skin surfaces.
INGESTION: Not likely to occur. Avoid breathing vapors.

V. Transport Information

IDENTIFICATION NUMBER: UN3257 PGIII

AGGREGATE / ASPHALT DELIVERY TICKET

A CRH COMPANY
2273 River Road
Grand Junction, CO 81505
Phone: (970) 243-4900
Fax: (970) 243-5945

DELIVERY DATE TIME	LEAVE PLANT	ARRIVE JOB	LEAVE JOB	ARRIVE PLANT

SOLD TO BUYER

JOB LOCATION

TICKET NO.

PLANT NO.

ORDER NO.

OPERATOR:
DRIVER ON ❑ OFF ❑

CUSTOMER/JOB NUMBER	TRUCK NUMBER	PAYMENT METHOD	ZONE NUMBER	CUSTOMER PURCHASE ORDER NUMBER

QUANTITY	PRODUCT CODE	PRODUCT DESCRIPTION	UNIT COST	AMOUNT

GROSS WEIGHT	- TARE WEIGHT	= NET WEIGHT		
TONS ORDERED	TONS DELIVERED	TONS REMAINING	SALES TAX	
			PLEASE ~ PAY THIS AMOUNT	

NOTICE TO BUYER / OWNER: Failure of the Contractor to pay the supplier for the materials and/or services to complete this contract can result in the filing of a Mechanics Lien on the property which is the subject of this contract pursuant to Colorado Revised Statutes Section 38-22-109 (3). To avoid this result you may ask this contractor for "Lien Waivers" from all persons supplying materials or services for the work described in the contract. Failure to secure Lien Waivers may result in your paying for labor and material twice.

SALES CONTRACT TERMS: Payment in full is due Net 30 Days following the invoice date. In the event payment is not make when due, I/We agree to pay reasonable collection fees, lien fees, and attorney fees with or without suit, together with a finance charge of 1 1/2% per month (18% annual rate) until paid. A charge of $25.00 will be assessed on all non-sufficient fund returned checks. Signature by buyer/owner/agent or receipt of material constitutes acceptance of above including Oldcastle SW Group Inc., dba United Companies credit terms.

STANDING AND UNLOADING TIME: All quotations are based on allowing 10 minutes free unloading time. Unloading time in excess of the above will be charged at the current rate. Call 970-243-4900 and ask for either the sand or gravel scalehouse or the asphalt plant for current rate information.

Notice: Our drivers will make every effort to place material where buyer/owner or agent designates, but the Company assumes no responsibility for damages inside curb or property line. Claims for shortage will not be allowed unless made at the time this material was picked up or delivered. It is the responsibility of the buyer/owner or agent to insure correct product has been picked up or delivered.

The undersigned acknowledges that he/she is the Buyer or an authorized agent for the Buyer and agrees, on behalf of the Buyer, to all terms and conditions set forth herein. Refusal to sign this delivery ticket BUT acceptance of material constitutes agreement with terms and conditions above.

Rec'd by _____

WE APPRECIATE YOUR BUSINESS

In the event buyer/owner or agent directs driver to dump materials in an area where the driver may become stuck, buyer/owner agrees to pay towing fees.

_____

ACCUMULATED CASH SALE THIS ORDER

To Reorder: CRHAmericas@AmericanBus.com

MATERIAL SAFETY DATA SHEET

OSHA 29 CFR 1910.1200

I. Product Identification

All Purpose Sand
All Purpose Gravel

II. Hazardous Ingredients/Identify Information

Hazardous Components CAS NO.
Silica Sand, Crystalline 14808-60-7
Other Limits: National Institute for Occupational Safety and Health (NIOSH) Recommended standard maximum permissible concentration = 0.05 mgfM3 (respirable free silica) as determined by a full-shift sample up to 10 hour working day. 40-hour work week. See NIOSH Criteria for a Recommended Standard Occupational Exposure to Crystalline Silica.

III. Health Hazard Data

This product contains silica particles that may be broken down to respirable size range during shipping, handling, or use, and thus may be inhaled.
Route(s) of Entry: Inhalation, Skin, Ingestion
Health Hazards (Acute and Chronic):

- -Contains Silica dust that can cause severe and permanent lung damage and other diseases.
- -Breathing silica dust can cause silicosis, a lung disease that can cause serious breathing difficulties and death.
- -Breathing silica dust may cause cancer.
- -Breathing silica dust may cause scleroderma, a scarring of the skin or internal organs.

Breathing silica dust may not cause noticeable injury or illness, even though permanent lung damage may be occurring.

IV. Emergency and First Aid Procedures

For sand in eyes, wash immediately with water. If irritation persists, seek medical attention. For gross inhalation, remove person immediately to fresh air, give artificial respiration as needed, and seek medical attention as needed.

V. Control Measures! Personal Protection

Inhalation: DO NOT BREATH DUST. In cases where the sand can be used in a damp condition, the most effective dust control measure is to keep the sand damp. Many uses of silica sand require it to be used in dry condition; in such cases PEL exposure limits may be exceeded. Local exhaust can be helpful to reduce airborne dust levels. When dust levels exceed PEL exposure limits, the use of an OSHA, MSA or NIOSH approved respirator is required. Respirator requirements are based on exposure level as shown below:

5 x PEL or less: Any dust respirator.

WARN EMPLOYEES AND/OR CUSTOMERS OF THE HAZARDS AND REQUIRED OSHA PRECAUTIONS ASSOCIATED WITH THE USE OF THIS PRODUCT.

I. Product Identification

Asphalt

II. Composition I Information on Ingredients

Asphalt

III. Potential Health Effects

INHALATION: Inhalation of hot asphalt vapors can produce eye and respiratory tract irritation, headache, nausea and nervousness.
EYE CONTACT: Vapors of hot asphalt may cause eye irritation.
SKIN CONTACT: Handling of hot asphalt can cause severe burns because it is sticky and not readily removed from skin. Vapors from hot asphalt may irritate the skin. Occasional contact with asphalt is not expected to have serious health effects; however repeated contact may cause dermatitis (skin Irritation).
INGESTION: Ingestion of cooled asphalt is relatively non-toxic.

IV. First-Aid Measures

INHALATION: Remove from further exposure. If unconsciousness occurs, seek immediate medical assistance. If breathing stops, use mouth-to-mouth resuscitation.
EYE CONTACT: Flush immediately with water for at least 15 minutes. Seek medical attention immediately.
SKIN CONTACT: If hot asphalt contacts exposed skin, cool immediately with cold water and seek medical assistance promptly. Exercise extreme care in removing contaminated clothing to avoid damage to skin surfaces.
INGESTION: Not likely to occur. Avoid breathing vapors.

V. Transport Information

IDENTIFICATION NUMBER: UN3257 PGIII